

# Autobahn Series ATBMIC

Roadway & Security Lighting

FAO Module

## FIELD ADJUSTABLE OUTPUT MODULE

### MVOLT

	FAO Position	% Lumens	% Wattage
10BLEDE60	1	35%	40%
	2	48%	51%
	3	61%	63%
	4	74%	75%
	5	87%	87%
	6	99%	99%
	7	100%	100%
	8	100%	100%
10BLEDE70	1	40%	45%
	2	55%	58%
	3	65%	67%
	4	80%	80%
	5	93%	93%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE85	1	39%	42%
	2	68%	68%
	3	70%	71%
	4	80%	80%
	5	92%	91%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE10	1	39%	41%
	2	56%	56%
	3	72%	69%
	4	89%	86%
	5	93%	92%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE13	1	46%	40%
	2	55%	43%
	3	63%	61%
	4	80%	75%
	5	90%	88%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE15	1	36%	34%
	2	48%	46%
	3	61%	59%
	4	74%	72%
	5	87%	85%
	6	99%	99%
	7	100%	100%
	8	100%	100%

### HVOLT

	FAO Position	% Current	% Wattage
10BLEDE60	1	37%	43%
	2	49%	55%
	3	63%	66%
	4	76%	78%
	5	89%	90%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE70	1	37%	42%
	2	49%	53%
	3	63%	65%
	4	76%	77%
	5	89%	89%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE85	1	37%	41%
	2	49%	52%
	3	63%	64%
	4	76%	77%
	5	89%	90%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE10	1	37%	40%
	2	50%	51%
	3	63%	64%
	4	76%	77%
	5	89%	89%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE13	1	37%	38%
	2	50%	50%
	3	63%	63%
	4	76%	75%
	5	89%	88%
	6	100%	100%
	7	100%	100%
	8	100%	100%
10BLEDE15	1	37%	37%
	2	50%	49%
	3	63%	62%
	4	76%	75%
	5	89%	88%
	6	100%	100%
	7	100%	100%
	8	100%	100%

### Field Adjustable Module

The Field Adjustable Output (FAO) module is an onboard device that adjusts the light output and input wattage to meet site specific requirements, allowing a single fixture configuration to be flexibly applied in many different applications.

